

Embedded Industrial mini PC 3½", Atom N2600, CF, 4
x USB, 2 x RS232 CAN-buss for eldre OS Windows 7,
XP Embedded og Linux

FEATURES

Anbefales ikke for nyere OS! Ingen støtte for
Windows 10/11

Kontakt oss angående utskifting
Brikkesettet er EOL

Atom 1,6 GHz CPU N2600

2 GB RAM DDR3, So-DIMM-sokkel

1 x RS232/422/485 med DB9-kontakt

1 x RS232/422/485/CAN med DB9-kontakt

VGA

4 x USB 2.0

2-inn/2-ut digital

2 x 10/100/1000 RJ45 ethernet

Mini SIM-spor

2,5" SSD/HDD-spor (harddisk IKKE inkludert)

DIN-skinneinstallering

9~32 VDC

Mål: 145 x 102 x 50 mm

Temperatur: 0 - +50°C

OS-støtte: Windows 7, XP Embedded og Linux



SPECIFICATIONS

CPU	:	Intel Atom-N2600 1.6GHz, 1MB L2 cache (Intel dual core CPU)
Chipset	:	NM10
Hukommelse	:	1 x 200-pin DDR3-RAM SO-DIMM. Monteret med 2GB RAM (maks. 2GB)
I/O	:	1 x Digital I/O tilslutning via 6 pin terminalblok. Tænd/sluk knap, 1 x Power LED, 1 x HDD LED 1 x PCIe Mini-card interface til trådløs eller GPRS modul
Lyd	:	1 x lydudtag via jack-stik til hovedtelefon
Montering	:	Mulighed for DIN skinne montage. Eller VESA 75*75 panel montering
Netværk	:	2 x 10/100/1000 Mbit m/RJ45-stik Realtek RTL8111F
OS SUPPORT	:	Understøtter Windows 7, XP Embedded og Linux
Porte	:	1 x RS232/422/485 med DB9-stik. 1 x RS232/422/485/CAN med DB9-stik
Strømforsyning	:	9~32 VDC, 35V A via 2 pin skrueterminal (benyt DC12V/5A-R-Q)
VGA	:	1 x VGA analog med DB15 tilslutning

