

UHF 865MHz RFID-leser, utendørs, med 2 - 5 m leseavstand, for passive UHF TAG-er, COM-port, SDK FEATURES

For passive UHF-brikker 865MHz
Støtter ISO18000-6B, ISO18000-6C
RF-effekt: 0,1 - 1 Watt
TAG-avlesning styres via programvarekommandoer
Grensesnitt: RS232, RS485 og Wiegand 26/32
Sirkulær polarisert antenne
RS-232, RS-485, Wiegand 26Bits/32Bits
5V DC strømforsyning / 2 Watt
Mål: 220 x 220 x 50 mm
Vekt: 1,5 kg
IP65



SPECIFICATIONS

Driftstemperatur	:	-35 til +65 °C
Forsyning	:	12 VDC, 2 A. 230VAC adapter medfølger
Frekvens	:	865-868 MHz
Hastighed	:	Op til 30 km/t på tværs af læsefelt
Interface	:	RS232, RS485 og Wiegand 26/34
Max læseafstand	:	Typisk 2 - 4 m, mere under ideelle forhold
Miljø	:	IP54 tæthed. Egnet til udendørs brug
Montering	:	Rørbeslag, justerbart horisontalt og vertikalt
Vertikal spredning	:	70°
Dimensioner	:	215 ´ 215 ´ 60 mm

