

1 x USB til RS232 / RS422 / RS485 adapter, optisk isolert

FEATURES

- får en RS485 eller RS422 eller RS232 port på PC via USB-porten
- Galvanisk skille (optisk) 2KV
- DB9 hann- og skruklemme til 232/422/485 forbindelse
- Terminering av Jumpers
- baud rate 300bit / s to 921,6 kbit / s
- valgbar RS232, RS422 og RS485 via DIP
- Støtter Win7 / 8/10 og over så vel som MAC drevet via USB (5V)
- Driftstemperatur . 0 ° til 55 ° C,



SPECIFICATIONS

USB	:	USB 2.0 High Speed, USB 1.1 compliant Speed 480Mbps, hi-speed USB
Driftstemperatur	:	0°C to 55°C (32°F to 131°F)
Approval	:	CE, FCC
Baudrate	:	Data Bits 7, 8 Parity None, Even, Odd, Mark, Space Stop Bit 1, 2 Flow Control Hardware (RTS, CTS), XON/XOFF
Isolation	:	25kV ESD protection for all signals 2000V DC optical isolation for all signals
Kabel	:	0,9 m
Kabel	:	USB kabel medfølger
Luftfugtighed	:	5% to 95% RH
Montering	:	DIN rail bracket
OS SUPPORT	:	Windows 2000 up to Windows 10 Windows Server 2000 up to 2018 Linux kernel 2.6+ Mac OS X support available
Porte	:	Max. Speed RS-232:up to 1Mbps RS-422/485:up to 3Mbps RS-232 Signals RxD, TxD, GND, RTS, CTS RS-422 Signals TxD-, TxD+, RxD+, RxD-, GND, RTS-, RTS+, CTS+, CTS- RS-485 Signals (4 wire) TxD-, TxD+, RxD+, RxD-, GND RS-485 Signals (2 wire) Data-, Data+, GND
Signaler	:	RS422/RS485



SPECIFICATIONS

Strømforsyning	:	Power Input Power supplied via USB connector No external power needed
	:	Power Output 5V, 150mA through pin 5 of terminal block
Temperatur	:	-20°C to 75°C (-4°F to 167°F)

