

PCI Express-kort for USB 3.1C. PCIE-kort med USB 3.1C

FEATURES

PCI Express Base Specification Revision 3.0 enkeltfelt (x1).
Kompatibel med Universal Serial Bus 3.1-spesifikasjonen Gen2.
Kompatibel med xHCI-spesifikasjonene (eXtensible Host Controller Interface) revisjon 1.1
Støtter samtidig bruk av flere USB 3.1-, 3.0-, USB 2.0- og USB 1.1-enheter
Støtter USB-dataoverføringshastighet på 10G/5G/480/12/1,5 Mbps.
Utvider én ekstern USB 3.1 Super Speed plus Type-C-port (DFP) på systemet.
USB-porten gir maksimalt +5V DC / 3000mA strømutgang til USB-enheten.
Innebygd overstrømsbeskyttelse på hver USB-port.
Støtter enhetens eksterne vekkefunksjon fra USB-tastatur eller mus.
Med hot swapping-funksjonen kan du koble til/fra en enhet uten å slå av systemet.
Driverstøtte for Microsoft Windows 7, 8.x og 10 operativsystemer
Sertifisert med elektromagnetisk kompatibilitet CE-, FCC-, VCCI-, C Tick-, BSMI- og RoHS-godkjenning.
Windows 11 64-bit
Windows 10 32/64-bit
Windows 8.1 32/64-bit
Windows 8.0 32/64-bit
Windows Server 2022 64-bit
Windows Server 2019 64-bit
Windows Server 2016 64-bit
Windows Server 2012 R2 64-bit
Windows Server 2012 64-bit



**DANBIT**

CNV-PCIE-USB3.1C

SPECIFICATIONS

OS SUPPORT	:	Windows 7, 8, 10. Linux 2.6.31 eller nyere
Porte	:	1x USB 3.1C



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.