

Ethernet til HART-omformer - Master. Tillater 2 Masters. Inngangsport.

FEATURES

- Støtter HART kort / lang ramme
- Støtter HART Burst-modus
- Støtter punkt-til-punkt eller multi-drop HART-modus
- Støtter tilkobling av opptil 15 HART-slaveenheter
- Tillat 2 HART-mestre
- HC_Tool-verktøyet for modulkonfigurasjon og HART-kommunikasjon
- Støtter fastvareoppdatering via Ethernet
- PWR / TxRx indikasjons-LED
- 4KV ESD-beskyttelse
- Innebygd vakthund
- Valgbar 250Ω belastningsmotstand
- 4 HART-kanaler
- Støtt VxComm-teknikk
- Innebygd webserver for nettverksinnstilling



SPECIFICATIONS

Driftstemperatur	:	-25 °C ~ +75 °C
Annen	:	Selectable 250 Ω terminal resistor for each HART port.Power reverse polarity protection, Over-voltage brown-out protection
Ethernet	:	10/100 Base-TX with Auto MDI/MDI-X
Isolation	:	500 VDC
Kanaler	:	4
LED	:	PWR : Power Indicator TxRx : Data Received from Ethernet / HART Indicator
Luftfugtighed	:	5% ~ 95% RH, non-condensing
Montering	:	DIN-Rail or Wall Mounting
Stik	:	2-pin screwed terminal block for each HART port

