

17" Panel-PC med stålfrent, Intel Core i3 / i5 / i7 med 2x PCIe-utvidelse (kan leveres med 1000 nits)

FEATURES

17" TFT-LCD 1280x1024

Panelmontering

Touch: Standard projisert kapasitiv, på bestilling:

Resistiv eller glass

Kontrast 800:1 standard (på bestilling: 1000:1 nits)

8. generasjon Intel Core Celeron, i3, i5, i7-støtte

1 x 260-pinners DDR4 SO-DIMM-sokkel opp til 32GB
2400MHz

4x USB 3.0 type A

2x GbE LAN

Lyd inn/ut

IP66 foran

1 x HDMI

1 x VGA

2x 2,5" SATA RAID 0,1,5 støtte

3x COM (1xDB9 RS-232/422/485, 1x DB9 RS232, 1x
DB9 RS-422/485)

1 x Mini PCIe full størrelse (PCIe/USB/SATA)

1 x Mini PCIe halv størrelse (PCIe/USB)

1x SIM-spor for (wifi/BT/4G)

1x PCIe1 og 1x PCIe x16 spor.

439 x 348 x 64,8 mm

CE/FCC klasse A

Arbeidstemperatur 0~50 grader

Mulighet for ekstern PÅ/AV via. 2-polet støpsel

Bredt område DC 9 ~ 36V strøminngang

Støtter Windows 10 IoT, Windows 11



SPECIFICATIONS

USB	:	4 x USB 3.0 Type A, 2 x USB 2.0 Type A by cable (option)
Approval	:	CE / FCC Class A
Ethernet	:	2 x GbE LAN RJ-45
Forsyning	:	DC 9~36Vdc
IP-Tæthed	:	Front IP 66
Luftfugtighed	:	10 to 90% @ 40°C, non- condensing
Lyd	:	1 x Mic-in, Line-out
OS SUPPORT	:	WIN 7, Windows 8.1, Windows 10 IOT Enterprise
Porte	:	1xDB9 RS232, 1xDB9RS232/422/485, 1x RS422/485
Skærm	:	LCD Size 17" TFT-LCD Max. resolution 1280 x 1024 Max. color 16.7M Luminance(cd/m ²) 350 Viewangle(H°/V°) 170 (H) / 160 (V) Contrast 1000: 1 Backlight lifetime(hrs) 30,000 hrs
Temperatur	:	Operating temperature(°C) 0~50°C Storage temperature(°C)
Touch	:	Touch Type Resistive Touch Screen/Projected Capacitive Touch Screen Interface USB Light transmission(%) Over 80%(Resistive) / Over 90%(Projected Capacitive)



**DANBIT**

IPP17-I8+PCIEX

SPECIFICATIONS

Dimensioner : 439x348x95mm



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.