

19" i5 ECDIS DNVGL-CG-0339, IACS E10 Marine- godkjent panel-PC, 24VDC

FEATURES

19" 1280 x 1024 Marine godkjent Panel PC
Projektiv multitouch-skjerm PCAP
Marin standard: DNVGL-CG-0339, IEC60945 4. IACS-
E10
Intel Core i5-5200U 2,2 GHz
4 GB RAM, 128 GB SSD (mSATA) Dual Ethernet
Støtter Win 10 IoT Enterprise (må kjøpes separat)
2 x USB 3.0, 1 x USB 2.0
1 x RS232 (RS422/485)
2 x RJ45
Alternativ: 8 lm DI/DO (ekstra kjøp)
Alternativ: 4 x NMEA 0183-port (ekstra kjøp)
Forsyningsspenning: 24VDC / 65Watt
DC-inngang: 9 - 36VDC
Mål: 429 x 382 x 73 mm
Vekt: 7,8 kg



SPECIFICATIONS

CPU	:	Intel Core i5-5200U Broadwell 2.2GHz
Digital I/O	:	8 Channel Isolated Digital Input/Output (Optional)
Driftstemperatur	:	-15 to 55 deg.C
Farve	:	16.7 M colors, 8 bits/color
Betragningsvinkel	:	85°/85°/80°/80° (typ.) (Up/Down/Left/Right)
Chok/Vibration	:	Anti-Vibration 0.7g@DNV2.4 (Class A) Anti Shock 15G, 11ms duration
Ethernet	:	Dual Ethernet Gb LAN, 2 x RJ45
Hukommelse	:	1 x DDR3L-1066 SODIMM (Default 4GB,Max 16GB)
Kontrast	:	1000:1 (typ.)
Luftfugtighed	:	5% to 95% (non condensing)
Lyd	:	Buzzer 75 dB~80 dB, 2300 Hz, 1m Speaker 2 x 2W Speaker
Pixels	:	0.294 (H) x 0.294 (V) mm



**DANBIT**

IPP19IDNV

SPECIFICATIONS

Strømforbrug : 80W

Strømforsyning : 24V DC-in with Isolation (9~36V acceptable), DC Power Signal 1 x 3-Pin Terminal Block (Phoenix type)



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.