DANBIT

M485-ETH-CAN

Ethernet til kan enhetsserver. CAN til Ethernet gateway. Med 1 x kan, RS232 og RS485.

FEATURES

- Internett-kommunikasjonskontroller med 1 x kan buss, 1 x Rs-232, 1 x RS-485 og 1 x Ethernet 10/100 Base-TX Ethernet Controller
- TCP / IP-protokoll
- 80 MHz CPU
- 1 x RS-232-port, 1 x RS-485-port og 1x-kan-port kan brukes samtidig
- Maksimal overføringshastighet på opptil 1M BPS for CAN og 115.2Kbps for RS-232 RS-485
- 7-SEGMENT LED-skjerm
- Programvarekonfigurasjon for CAN og RS-232
- Webkonfigurasjon
- Opptil 25 Ethernet Client Connections
- Støtter Virtual COM

Danbit A/S Schous plass 1 Oslo, N-0552 Norway | 67 104 460 | salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.

DANBIT

M485-ETH-CAN

SPECIFICATIONS

Driftstemperatur	:	-25 ~ 75 ℃
Controller	:	10/100Base-TX Ethernet Controller (Auto-negotiating, Auto_MDIX) Connector RJ-45 with LED indicator
Forsyning	:	Power supply Unregulated +10 ~ +30 VDC Protection Power reverse polarity protection, Over-voltage brown-out protection Power Consumption 2.5 W
Isolation	:	1000 VDC for DC-to-DC, 2500 Vrms for photo-couple
Montering	:	DIN-Rail
Stik	:	CAN BUS: 2-pin screwed terminal block. COM 1 Connector 5-pin screwed terminal block (TxD, RxD, RTS, CTS, GND). COM 2 Connector 2-pin screwed terminal block (DATA+, DATA-)
Dimensioner	:	(W x L x H) 72mm x 122mm x 33mm

Danbit A/S Schous plass 1 Oslo, N-0552 Norway | 67 104 460 | salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.