

4 PORTS 10/100 / 1000MBIT RJ45 + 2 PORTER 100 / 1000MBIT SFP Slot, administrert switch, 12 - 48VDC og 24VAC

FEATURES

- Fast Ring, Redundant Ring of kritiske nettverk
- IEEE 1588 Time Protocol, støtter MEF service og synkron Ethernet
- Støtter MODBUS TCP-protokollen
- Støtter IGMP snooping 4 x 10/100 / 1000Mbps RJ45-porter
- 2 x 100 / 1000mbit SFP-porter
- 12 - 48VDC, redundant inngangs
- 24 VAC forsyningsspenningen er også mulig
- IP30 metallhus med DIN brakett
- temperaturområde fra -40 til + 75 ° C,



SPECIFICATIONS

Driftstemperatur	:	-40 - 75°
Forsyning	:	Dual 12~48V DC 24V AC
Materiale	:	IP30 metal case
Montering	:	DIN rail kit and wall-mount kit
Porte	:	4 10/100/1000BASE-T RJ45 auto-MDI/MDI-X ports
Slot	:	2 1000BASE-SX/LX/BX SFP interfaces (Port-5 to Port-6) Compatible with 100BASE-FX SFP
Stik	:	Removable 6-pin terminal block for power input Pin 1/2 for Power 1, Pin 3/4 for fault alarm, Pin 5/6 for Power 2
VLAN	:	802.1Q tagged based VLAN, up to 255 VLAN groups Q-in-Q tunneling Private VLAN Edge (PVE) MAC-based VLAN Protocol-based VLAN Voice VLAN MVR (Multicast VLAN Registration) Up to 255 VLAN groups, out of 4094 VLAN IDs
Dimensioner	:	32 x 87x 135 mm

