

M485-DIO7D-I

7 digitale innganger og 8 digitale utganger, display.
RS485 buss. 10 - 30VDC.

FEATURES

- RS485 Modul med digital I / O
- 7 Digital Input
- 8 Digital Output, 30Volt / 30mA
- RS485 Interface
- Baudrate 1200 ~ 115200 bps
- Dual Watchdog
- 10 - 30 VDC, 1 W Via Terminal Block
- 25- + 75 °
- DIN Rail Montering



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

SPECIFICATIONS

Driftstemperatur	:	25 ~ +75°C
Baudrate	:	1200 ~ 115200 bps
Indgang	:	7 stk. med fælles minus. Indbyggede Pull-up": 10 kΩ til 5 VDC Logisk 0: 0 - 1 V Logisk 1: 4 - 30 V
Interface	:	RS-485
LED	:	Yes, 1 LED as Power/Communication Indicator
Montering	:	DIN-Rail or Wall Mounting
Protokol	:	DCON (For I-7050 series) Modbus RTU, DCON (For M-7050 series)
Udgange	:	8 stk. "Open collector": 30 V/30 mA, maks. effekt: 300 mW
Watchdog	:	Dual Watchdog. Module (1.6 Seconds), Communication (Programmable)

