

19 "DNV Marine Approved Panel Monitor, Supply 24Vdc, 5: 4 Format

FEATURES

19 "DNV2.4, IEC60945 Marine Monitor uten berøring
400 nits
IP66
Oppløsning: 1280x1024 - 5:4 Format
Aktivt visningsområde: 376,32 (H) x 301,06 (V) mm
1 x kompositt (RCA phono)
1 x DVI-D
1 x S-Video (SVHS)
1 x RGB (D-SUB)
Strømforsyning: Rekkeklemme 24V DC
Montering: Panel (Innmurt) montering med IP66 *,
VESA, Brakett montering
Antivibrasjon: 5Hz - 500Hz / 1Grms / 3Axis
Antisjokk: 15G, 11ms varighet
Valgfritt: AC-strømsignal Std IEC-inngang
Valgfritt: Berøringsskjerm D-SUB 9P Hun
Valgfritt: Fjernkontroll via RS232 D-SUB 9P



SPECIFICATIONS

Driftstemperatur	:	-15 ~ +55°C
Approval	:	DNV2.4,IEC60945,IACS-E10,CE,FCC
Betjening	:	Power On/Off via Front Button, VR Brightness Knob Control
Chok/Vibration	:	Anti-Vibration 5Hz~500Hz / 1Grms/3 Axis Anti Shock 15G, 11ms duration
Grafik	:	19", Res 1280 x 1024, Pixel Pitch (RGB) 0.294 (H) x 0.294 (V) Contrast Ratio 1000:1 (typ.) Brightness 400 (typ.) Viewing Angle -85~85 (H); -80~80 (V) Active Display Area 376.32 (H) x 301.06 (V) Max Colors 16.7M (8bits/ colors)
Indikatorer og kontakter	:	LED indicators Power Mode Status LED
IP-Tæthed	:	Front IP66, (saw touch IP54)
Luftfugtighed	:	5% to 95% (non-condensing)
Montering	:	Vesa, and stand (stand bracket is option)
OSD	:	On Screen Display control (OSD)
Skærm	:	19" Transflective
Strømforsyning	:	24Vdc DC Power Signal Screw terminal block



**DANBIT**

MON-MAR19"

SPECIFICATIONS

Vekt : 5.4 Kg



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.