

ETH2SER5230A

2 Ports Serial Port Server RS422 / 485 Optoisolated, Moxa Nport 5230A-T. Serial Device Server. FEATURES

Eksterne COM-porter via Ethernet og Internett
Seriell enhetsserver med RS422 eller RS485 via
Ethernet og Internett.
RS422 / 485 SeriePort via skrueterminal
DUAL DC POWER INPUT MED POWER JACK OG
Terminal blokk
strømforsyninger fra 12 - 48VDC
DIN montering



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

SPECIFICATIONS

Driftstemperatur	:	0 to 60°C
Annen	:	Ethernet Line Protection EN 61000-4-5 (Surge) Level 2
Forsyning	:	Power Requirements Input Voltage 12 to 48 VDC Input Current 119 mA @ 12 VDC
Hastighed	:	10/100 Mbps, auto MDI/MDIX
Isolation	:	1.5 kV built-in
Materiale	:	Metal
Porte	:	2
Protokol	:	Network Protocols ICMP, IPv4, TCP, UDP, DHCP, BOOTP, Telnet, DNS, SNMP V1, HTTP, SMTP, IGMP V1/2, ARP
Signaler	:	RS-422 Tx+, Tx-, Rx+, Rx-, GND RS-485-4w Tx+, Tx-, Rx+, Rx-, GND RS-485-2w Data+, Data-, GND
Stik	:	8-pin RJ45
Watchdog	:	Built-in WDT (watchdog timer)
Vekt	:	340 g



**DANBIT**

ETH2SER5230A

SPECIFICATIONS



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.