

12,1 "LCD-berøringsskjem, lesbar i lyst sollys, IP65 foran, VGA, 4: 3-format

FEATURES

- 12,1 "LCD-skjerm
- IP65 nær fronten
- Oppløsning 1024 x 768, 4: 3-format
- 800: 1
- 1 x VGA grensesnitt for 5-tråds resistive touch-skjerm
- 300 nits
- 12V DC inngang
- inngang: 110 - 240V
- Utgang: 12VDC
- Driftstemperatur: -20 - 70C VESA kirke og påbyggings
- Valgfritt: 1000 nits
- Valgfritt: DVI
- valgfritt: display Port
- valgfritt: USB for berøring
- valgfritt: HDMI



SPECIFICATIONS

Driftstemperatur	:	0-50°C
Antal farver	:	16.2M (8 bits / color)
Betragningsvinkel	:	Viewing Angle : -80 ~ 80 (H); -70 ~ 70(V)
Forsyning	:	Power Adapter : 1 x ext. 100~220V AC to DC 12V adapter
Interface	:	1 x VGA D-Sub 15 pin
Kontrast	:	Contrast Ratio : 800 : 1 (typ.)
Lysstyrke	:	Brightness : 500 nits (cd/m2)
Montering	:	VESA DPMS compliant
Opløsning	:	1024 x 768 @ 60Hz, 75Hz
OSD	:	OSD Input : 5-key OSD buttons • OSD Function : Contrast, Color, Position, Auto-adjustment, Factory Settings
Pixels	:	0.24(H) x 0.24(V)
Skærm	:	12.1" LCD





DANBIT

MON12-LPM-RHB

SPECIFICATIONS



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.