

Intelligent CANBUS 2.0A og 2.0B til 10/100 Base-TX Ethernet / Modbus TCP/IP / Modbus RTU Konverter FEATURES

Intelligent Can for Modbus TCP / IP Converter
Støtter begge CAN spesifikasjon 2.0A og 2.0b
Maksimal overføringshastighet på opptil 1M bps for CAN og 115.2 Kbps for RS-232 RS-485
Maksimal overføring Avstand på kan over 1000m (følg kanen spesifikasjonen)
7-segment LED-skjerm for modul IP, RS-232 Baud Rate, CAN Configuration ...
Støtter Web Configuration
Støtter Maksimal 24 Ethernet Clients Connection < BR> MODBUS TCP / RTU-kommando for lesing og skriving Kan beskjed
Transparent kommunikasjon mellom kanenes enheter via Ethernet
30 spesifikke CAN ID-er i MODBUS TCP / RTU mode
DIN monteringen



SPECIFICATIONS

Driftstemperatur	:	-25 ~ 75 °C
Annen	:	Terminator Resistor Jumper for 120 Ω terminator resistor Specification ISO-11898-2, CAN 2.0A and CAN 2.0B
Ethernet	:	10/100Base-TX Ethernet Controller (Auto-negotiating, Auto_MDIX) Connector RJ-45 with LED indicator
Forsyning	:	Unregulated +10 ~ +30 VDC
Isolation	:	1000 VDC for DC-to-DC, 2500 Vrms for photo-couple
Montering	:	DIN-Rail
Porte	:	COM 1 RS-232 COM 1 Connector 5-pin screwed terminal block (TxD, RxD, RTS, CTS, GND) COM 2 RS-485 (Self-turner inside) COM 2 Connector 2-pin screwed terminal block (DATA+, DATA-)
RAID niveau	:	CAN, Ethernet, Modbus RTU, Modbus TCP
Stik	:	CANBUS: Connector 2-pin screwed terminal block (CAN_L, CAN_H)
Dimensioner	:	72mm x 122mm x 33mm (W x L x H)

