

ANR-LNX-0501G-SFP-T

4 porter Industriell 10/100 / 1000Mbit + 1 x 100 /
1000Mbit SFP sperrebryter, DIN-montering, -40 - + 75
° C, 12 - 48VDC

FEATURES

- 4 x 10/100/1000Mbps Ethernet porte + 1 x 100/1000Mbps SFP Slot
- Auto MDI/MDI-X Function
- Store-and-Forward Switching Architecture
- 10Gbps Back-Plane (Switching Fabric)
- 8K MAC Address Table
- 9.6Kbytes Jumbo Frame Support
- Surge Protection: 3kV
- ESD Protection: 6kV
- Redundant Power Input Design - 12~48VDC
- 1 Relay Output til Port Break Alarm
- IP30 Aluminumkabinet
- DIN-Rail og Wall Mount
- Temperaturområde: -40° to 75°C



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

SPECIFICATIONS

Driftstemperatur	:	-40 - +75
Fiber	:	1 x 100/1000Mbps SFP slot
Kabinet	:	Metal, IP30, DIN-beslag, option vægbeslag
Maks. effekt	:	5 Watt
Netværk	:	4 x RJ45, 10/100/1000Mbps
Dimensioner	:	30 x 99 x 142mm

