

ANR-LNX-0702G-SFP

5 porter Industriell 10/100 / 1000Mbit + 2 x 100 /
1000Mbit SFP sperrebryter, DIN-montering, -10 - + 70
° C, 12 - 48VDC

FEATURES

- 5 x 10/100 / 1000Mbps Ethernet-porter + 2 x 100 / 1000Mbps SFP-spor
- Auto MDI / MDI-X Funksjon
- Lagre og videresende byttearkitektur
- 10Gbps Back-Plan (Switching Fabric)
- 8K MAC Adressetabell
- 9.6Kbytes Jumbo Frame Support
- Overspenningsvern: 3kV
- ESD Protection: 6kV
- Redundant Strøminngang Design - 12 ~ 48VDC
- 1 Relé Utgang til Port Break Alarm
- IP30 Aluminiumskap
- DIN-Rail og Wall Mount
- Temperaturområde: -10 - 70 ° C



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

ANR-LNX-0702G-SFP

SPECIFICATIONS

Driftstemperatur	:	-10 - +70
Fiber	:	2 x 100/1000Mbps SFP slot
Kabinet	:	Metal, IP30, DIN-beslag, option vægbeslag
Maks. effekt	:	9,1 Watt
Netværk	:	5 x RJ45 10/100/1000Mbps



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk