

ANR-LNX-1604G-SFP-T

12 ports Industriel 10/100/1000Mbit + 4 x
100/1000Mbit SFP slot switch, DIN-beslag, -40 -
+75°C, 12 - 48VDC

FEATURES

- 12 x 10/100/1000Mbps + 4 x 100/1000Mbps SFP porte
- Auto MDI/MDI-X Function
- Store-and-Forward Switching Architecture
- 8K MAC Address tabel
- Jumbo Frame Support: 12.2K
- Surge Protection: 2,000 VDC Support
- ESD Protection: 6,000 VDC Support
- Redundant Power Input Design: 12~48VDC
- 1 Relay Output til Power Failure Warning
- IP30 Rugged Metal Case Design
- DIN-Rail and Wall Mount Support
- Udvidet temperaturområde: -40° to 75° C



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

SPECIFICATIONS

Driftstemperatur	:	-40 - +75C
Fiber	:	4 x 100/1000Mbps SFP slot
Forsyning	:	12 - 48VDC, redundant
Kabinet	:	Metal, IP30, DIN-beslag,
Maks. effekt	:	16 Watt
Netværk	:	12 x RJ45, 10/100/1000Mbps
Dimensioner	:	59 x 99 x 142mm

