

5 porter Industriell 10/100 / 1000Mbit bryter + 2 x Gbit SFP-spor, PoE + (30W), DIN-montering, -40 - + 85 ° C, 48 - 55VDC

FEATURES

- 4 x 10/100 / 1000Mbit, PoE + (30W) IEEE 802.3at
- 1 x 10/100 / 1000Mbit og 2 x 100 / 1000Mbit SFP-spor
- 14Gbps tilbakevannnsplan
- 8K MAC Adressebord
- 10,0 Kbytes Jumbo Frame
- Overspenning 2kV DC
- ESD-beskyttelse 6kV DC
- Redundant Power Input Design: 48 - 55VDC
- 1 Relé Utgang for Power Error Alarm
- IP30 Robust Metal Skap
- DIN-skinne og veggmontering inkludert
- Utvidet driftstemperatur: -40 - + 85 ° C



SPECIFICATIONS

Driftstemperatur	:	-40 - +85°C
Fiber	:	2 x 1Gbps SFP slot
Forsyning	:	48 - 55VDC
Kabinet	:	Metal, IP30, DIN-beslag,
Maks. effekt	:	110 Watt@48VDC, 130 Watt@51-55VDC, maks. PoE
Netværk	:	4 x RJ45 10/100/1000Mbps PoE+, 1 RJ45 x 10/100/1000Mbps
PoE	:	30 Watt
Dimensioner	:	46 x 142 x 99mm

