

ANR-LNP-0702G-SFP-24

5 porter Industriell 10/100 / 1000Mbit bryter + 2 x Gbit SFP-spor, PoE + (30W), DIN-montering, -10 - + 70 ° C, 12 - 36VDC

FEATURES

- 4 x 10/100 / 1000Mbit, PoE + (30W) IEEE 802.3at
- 1 x 10/100 / 1000Mbit og 2 x 100 / 1000Mbit SFP-sperre
- 14Gbps tilbakevannsplan
- 8K MAC Adresse Tabell
- 10,0 Kbytes Jumbo Frame
- Overvolt 2kV DC
- ESD Beskyttelse 6kV DC
- Redundant Power Input Design: 12 - 36VDC
- 1 Relé Utgang for Power Error Alarm
- IP30 Robust Metal Skap
- DIN-skinne og veggmontering inkludert
- Utvidet driftstemperatur: -10 - + 70 ° C



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

SPECIFICATIONS

Driftstemperatur	:	-10 - +70°C
Fiber	:	2 x 1Gbps SFP slot
Forsyning	:	12 - 36VDC, redundant
Kabinet	:	Metal, IP30, DIN-beslag,
Maks. effekt	:	145 Watt, maks. PoE
Netværk	:	4 x RJ45 10/100/1000Mbps PoE+, 1 RJ45 x 10/100/1000Mbps
PoE	:	30 Watt
Dimensioner	:	46 x 142 x 99mm

