

KVM-forlenger over IP med høy sikkerhet og kryptert fjernadministrasjon

FEATURES

- Høytytelses KVM over IP for ekstern serveradministrasjon
- Støtte for virtuelle medier (via USB)
- Høytytende video
- 10/100 MB Ethernet-port
- USB- eller PS/2-tastatur- og muskontakt
- Opptil 16 enheter kan monteres i 2U-rackplass
- Bruker Ekte VNC
- 16 brukere med tilgangsløpping
- Drevet via tilkoblet PC eller ekstern strømforsyning
- 100-240 VAC 50-60 Hz



SPECIFICATIONS

Driftstemperatur	:	0 - 40°
Annen	:	Supports exclusive access mode or up to four simultaneous connections
Forsyning	:	100-240 VAC 50 - 60Hz
Materiale	:	Compact case, robust metal construction
Netværk	:	Ethernet: RJ45 10/100 autosensing
Opløsning	:	up to resolutions of 1600 x 1200 with scalable viewer.
OS SUPPORT	:	All known software and operating systems including Windows (all), DOS, Linux, Unix, BSD, Sun OS, Solaris, Mac OS, NetWare etc
Stik	:	Video: HDD15, Keyboard/Mouse: MiniDIN6 1m 3-in-1 cable supplied (USB converters also included)
Vekt	:	0.34kg
Dimensioner	:	120mm/4.72 (w), 27mm/1.06 (h), 75mm/2.95 (d)

