

Digital KVM-forlenger over IP med DVI, USB og lyd,
høy sikkerhet, kryptert fjernadministrasjon

FEATURES

- Digital KVM over IP for ekstern serveradministrasjon
- Støtte for virtuelle medier (via USB)
- Høy ytelse DVI-D
- 1 x 10/100 MB Ethernet
- 2 x USB 2.0
- 1 x DVI enkeltledd
- 1 x RS232
- 1 x lyd/jackplugg
- Drives via USB eller ekstern PSU



SPECIFICATIONS

Driftstemperatur	:	0 - 40°
Annen	:	uses Real VNC client software that is specifically designed for secure, high performance KVM over IP applications and supports both IPV4 and IPV6 addresses.
Forsyning	:	Interface powered via two USB cables Externally powered from 100-240VAC, 47/63Hz- 5v - 2.5amp
Materiale	:	Compact case, robust metal construction
Opløsning	:	up to resolutions of 1920x1200 with scalable viewer
OS SUPPORT	:	All known software and operating systems including Windows (all), DOS, Linux, Unix, BSD, Sun OS, Solaris, Mac OS, NetWare, etc.
Stik	:	Video: DVI Single link USB 2.0 Type B connectors Ethernet: RJ45 10/100 auto sensing RS232: 6p6c connector
Vekt	:	0.34kg
Dimensioner	:	120mm/4.72" (w), 27mm/1.06" (h), 75mm/2.95" (d)



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk