

3 kVA / 2,4 kW UPS med LCD-skjerm. 19" Rack / Tower. Ekte sinuskurve, inkl. batteriboks for 6 stk. 12V/55Ah. 10 timer m/200W

FEATURES

- Toppklasse 3.0 kVA / 2,4 kW online UPS / nødkraft
- Input: 110-300 VAC 40Hz-70 Hz
- Utgangsspenning: 230 VAC / 50Hz
- LCD-skjerm
- Enfase
- Ekte Sine Curves - gir mindre lyd på utgangsspenningen
- Rack / Tower 2 i 1
- Innebygd inngang OVCD
- Fod / stativ eller rackmontering
- 1 x IEC 320 C20 Terminal (inngang)
- 4 x IEC 320 C13 (utgang)
- Godkjenninger: IEC 62040-1 (sikkerhet)
- IEC-62040-2 (EMC)
- Inkl. batteripakke: 6 x 12V / 55Ah



SPECIFICATIONS

Driftstemperatur	:	0-40°C
Alarm	:	Battery Mode Sounding every 4 seconds Low Battery Sounding every second Overload Sounding twice every second Fault Continously sounding
Annen	:	Optional SNMP Power management from SNMP manager and web browser
Batteri	:	6 x 12V/55Ah
Input	:	110-300 VAC 40Hz ~ 70 Hz
Interface	:	Interface to pc via Smart RS-232 / USB
Kapacitet	:	3.0 kVA / 2,4 kW
LED	:	Load level, Battery level, AC mode, Battery mode, Bypass mode, and Fault indicators
Montering	:	stander or 19" rack
OS SUPPORT	:	Windows 2000/2003/XP/Vista/2008/7, Linux, Unix, and MAC
Output	:	230 VAC
Software	:	Included



SPECIFICATIONS

Standarder	:	IEC 62040-1 (safety) & IEC-62040-2 (EMC)
Stik	:	1 x IEC 320 C20 Terminal (input) 4 x IEC 320 C13 (output)
Støj	:	Less than 50dBa by 1 Meter
Vekt	:	10 kg without batterypack
Dimensioner	:	480 (D) x 438 (W) x 88 (H) (2U) without batterypack

