

24 porter Industriell 10/100 / 1000Mbit + 4 x 100 /
1000Mbit SFP, managed, PoE-bryter. Rack. -40 - + 75
° C, 46 - 57VDC

FEATURES

24 x 10/100 / 1000Tx IEEE 802.3 Av / På, PoE +
Gigabit Porte (30W / Port) + 4 x Gigabit Kobber /
SFP Combi Ports
4 x 10/100 / 1000Tx RJ45 + 4 x 100/1000 SFP Slots:
Ledelse: SNMP v1 / v2c / v3, WEB, Telnet, Standard
MIB
Sikkerhet: 802.1x (Portbasert, MD5 / TLS / TTLS /
PEAP-kryptering), HTTPS, SSH og SNMPv3
Redundant : Proprietary Ring (Ultra High Speed
Recovery Time <20 ms), RSTP / STP (802.1w / 1D),
MSTP <48VDC Power Input (46-57 VDC for PoE off,
53-57 VDC anbefales for PoE ved) 2 Relé Utganger
Temperatur: -40 ° - 75 ° C - Polaritetsbeskyttelse -
Overbelastningsbeskytter
1U Rack Mount Design
IP30 Lukk



SPECIFICATIONS

Driftstemperatur	:	-40 - +75
Fiber	:	4 x 100/1000Mbps SFP slot
Forsyning	:	46 - 57VDC, redundant
Kabinet	:	1U, 19" rack, metal, IP30
Maks. effekt	:	20 Watt system, 30 Watt per PoE port, maks. 480 Watt
Netværk	:	24 x 10/100/1000Mbps, RJ45, PoE+
Protokol	:	IGMP, SNMP, TFTP, SNMP, SMTP, Syslog, Web-browser, Ring, IPv6
Dimensioner	:	438 x 43,6 x 259,2mm, 1U, rack

