

8-tommers LCD-skjerm, berøring med LED-baklys,
IP55 nær front, 800nits, lesbar i sollys, -20°C til
+60°C, 4:3 format

FEATURES

- 8" TFT LCD-skjerm, egnet for kjøretøy
- Resistive Touch (USB)
- LED-bakgrunnsbelysning
- 800 x 600 piksler (SVGA)
- Lysstyrke: 800 cd/m² (800nits)
- Lesbar i sollys
- Kontrast 500:1
- 1 x SD / MMC / MS kortleser, 1 x USB A, 1 x Mikrofon
- I DVI-tilkobling (VGA, 1 x USB og 1 x 12VDC)
- Tilførsel 9-36VDC, 15W
- Driftstemperatur -20°C til 60°C
- IP55 Front
- For VESA 75, Panel Power. veggmontering
- Dimensjoner: 207mm x 173mm x 36.7mm (B x H x D)



SPECIFICATIONS

Annen	:	2 x Built-in speakers (1.2W)
Chok/Vibration	:	Vibration (random): 2.5g@5 ~ 500 Hz □ Vibration Operating: MIL-ST-810G, 514.6 Procedure 1, Category 4, Ground Vehicle - Highway Truck Storage: MIL-STD-810G, 514.6 Procedure 1, Category 4, Integrity Test □ Shock
Dimensioner	:	207mm (W) x 173mm (H) x 36.7mm (D)
Driftstemperatur	:	-20°C to 60°
Interface	:	Lateral: 1 x SD/MMC/MS card reader, 1 x USB type A Host, 1 x Line-out 1 x Mic-in Interface Bottom: 1 x Mic-out, 1 x Line-in, 1 x DVI-D Connector (integrating VGA, USB x 1 and 12VDC x 1)
IP-Tæthed	:	Front panel IP55
Kontrast	:	Contrast ratio: 500 : 1 (typical)
Lysfølsomhed	:	Sunlight-Readable Display with High Brightness LCD (800 cd/m ²)
Materiale	:	Enclosure: Plastic PC + ABS
Montering	:	VESA 75, panel and wall mounting
Pixels	:	
Skærm	:	8" SVGA TFT LCD Monitor



MON8-TFT-S

SPECIFICATIONS

Vekt : 0.7Kg