

1 Unit Server til 19 "Rack Montering med 2 x PCIEX (X8) Utvidelse, SIM, 4XRS232 / 422/485, 4xUSB FEATURES

- 6th / 7th Gen Intel® Skylake-S / Kaby Lake-S I7 / I3 CPU
- Intel® Q170 Express Chipset
- 2 x DDR4 Sodimol Socket, Max. 64GB
- Flere uafhængige display: DP, HDMI DVI
- 2 x Intel Gbe LAN
- 4 x USB 3.0
- 4 x com
- 2 x PCIE x 8
- 2 x Mini PCIe (Option: 1xPCI, 1xPCIex)
- 1 x M.2
- 2 x SIM
- 1U Rackmount Server Design



SPECIFICATIONS

CPU	:	6th / 7th Gen Intel® Skylake-S / Kaby Lake-S i7 / i5 / i3 CPU
Chipset	:	Intel® Q170
USB	:	4 x USB 3.0
Driftstemperatur	:	(100 % CPU usage) -20°C to +60°C with mSATA / SSD 0°C to +50°C with HDD
Annen	:	OPTIONS GPS, Bluetooth, PoE, WiFi, 4G LTE, Isolated COM, battery UPS, DI/DO, Video Input *SATA Kit * Power adapter / Power Supply
Ethernet	:	2 x RJ45 Intel GbE
Forsyning	:	12Vdc external adapter 100/240Vac to DC 120W, Internal 150Watt
Hukommelse	:	2 x DDR4 SODIMM, Max. 64GB
Luftfugtighed	:	95% @ 40°C, non-condensing
Msata	:	storage
OS SUPPORT	:	7th Gen. Win10 IOT (64bit), Ubuntu 16.04.3 above, Fedora 26 above, CentOS 7.4 above 6th Gen. Win 10 IOT (64bit), Win 8.1 (64bit), Win Emb. 8 (64bit), Win. 7 (64bit), mbedded Sta 7 (64bit), Ubuntu 16.04.3 above, Fedora 26 above, CentOS 7.4 above
Porte	:	4 x RS232 / 422 / 485



SPECIFICATIONS

Udgange	:	1 x DP, 1 x HDMI, 1 x DVI
Udvidelser	:	2 x PCIe x 8 (Optional) 1 x Full-size Mini PCIe (PCIe / mSATA / USB) 1 x Full-size Mini PCIe (PCIe / USB)
Dimensioner	:	(WxDxH) 440W x 360D x 44.3H mm(WxDxH) 440W x 360D x 44.3H mm

