

M485-REP2-I

RS485 repeater, 1200m, 300 - 115,2kBit/s, dobbel
opto-isolert, 10 - 30VDC, -25 - +75°C

FEATURES

- Optoisoleret RS-485 repeater
- 2 vejs 3000 VDC isolation
- ESD-beskyttelse til RS-485
- Baud-hastighed 300 bit/s til 115.200 bit/s
- Understøtter effektindtag på +10 V DC til +30 V DC
- Driftstemperatur: -25° til +75°C
- Til DIN skinne montering



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

SPECIFICATIONS

Driftstemperatur	:	-25 °C ~ +75 °C
Forsyning	:	Input Voltage Range +10 VDC ~ +30 VDC (Non-isolated) Power Consumption 2.16 W
Hastighed	:	300 ~ 115200 bps
Interface	:	RS-485 Data+, Data
Isolation	:	3000 VDC Isolated Voltage 2-way Isolated
Montering	:	DIN rail or wall
Overførselshastighed	:	Max. 1,200 m at 9.6 kbps; Max. 400 m at 115.2 kbps (Belden 9841 2P twisted-pair cable, if different cables are used, the transmission distance may change)
Stik	:	Removable 10-Pin Terminal Block x 2
Dimensioner	:	(W x H x D) 72 mm x 122 mm x 35 mm

