

7" Robust nettbrett for bilmontering, kapasitiv multi-touch, 500 nits, FEATURES

- Intel® Atom™ E3815 1,46 GHz
- 2 GB DDR3L SODIMM; mSATA og Micro SD-spor
- 500 nits med automatisk dimming
- Kapasitiv multi-touch (PCT)
- 5 x programmerbare knapper
- 2 x volumjusteringsknapper
- 1 x RS-232, 1 x RS232/422/485
- 2 x USB (3.0, 2.0)
- 1 x Dual Micro SIM-spor
- 1 x CAN-buss (støttet SAE J1939)
- 1 x Gigabit Ethernet (RJ45)
- IEC 60529 IP65 (unntatt bunn I/O)
- Vibrasjon (under drift): MIL-STD-810G, metode 514.7 c2/c3/c4
- Sjokk (under drift): MIL-STD-810G, 40G ved 11 ms terminal/sagtann
- 30°C til +60°C
- 9~36 VDC inngang
- Kraftbeskyttelse for kjøretøy (ISO 7637-2)
- Windows 10 IoT



SPECIFICATIONS

CPU	:	Intel® Atom™ E3815 1.46GHz
Driftstemperatur	:	-30°C to +60°C
Batteri	:	UPS backup battery
Harddisk	:	mSATA and Micro SD slot
Hukommelse	:	2GB DDR3L SODIMM
I/O	:	1 x RS-232, 1 x RS232/422/485 2 x USB (3.0, 2.0) 1 x Dual Micro SIM slot 1 x CAN bus (SAE J1939 supported) 1 x Gigabit Ethernet (RJ45)
IP-Tæthed	:	IEC 60529 IP65 (except bottom side I/O)
Kontrast	:	500 nits support auto-dimming
Netværk	:	Gigabit Ethernet (RJ45)
Skærm	:	7" WSVGA TFT LCD (1024 x 600)
Touch	:	Capacitive multi-touch (PCT)

