

Trådløst industrielt WLAN opp til 150 Mbps, 2,4 GHz,
9-48V DC,

FEATURES

- WLAN opptil 150 Mbps (enkeltradio 2,4 GHz)
- Industriell 1x1 SISO (Single Input Single Output)
- IEEE 802.11 b/g/n
- 2 x 10/100Base-TX WAN/LAN-porter
- Brikkesett: Qualcomm/Atheros AR9331 SoC
- Tx Power (EIRP) 21 dB for 2,4 GHz
- 5 dBi dipol antenne
- WPA, WPA2, TKIP, AES
- Strøminngang: 9 - 48VDC / 2W, 4-pinners terminalblokk
- Beskyttelse mot omvendt polaritet
- IP30 forseglet kapsling
- DIN-skinne og veggmontering
- Driftstemperatur: 0°C til 60°C
- Vekt: 1 kg
- Mål: 26 x 95 x 75 mm



SPECIFICATIONS

Driftstemperatur	:	-40°C to 75°C
Antenne	:	One External SMA Antenna: 3dBi for 2.4GHz (SISO)
Approval	:	EMI, EMS, RF, RF Radiation Exposure, EN60950-1 CNS14336-1, RoHS Compliant
I/O	:	2*10/100BasetT(X), auto negotiation speed, Full/Half Duplex Mode
IP-Tæthed	:	IP30
Luftfugtighed	:	10% to 90%, (non-condensing)
Montering	:	DIN-Rail eller væg montering
Netværk	:	US/TW: 2.412G~2.462GHz EU/AU/NZ: 2.412G~2.472GHz
Protokol	:	IP, TCP, UDP, ARP, BOOTP, ICMP, HTTP, HTTPS, DNS Proxy, NTP, RADIUS, Dynamic DNS, SNMP
Standarder	:	IEEE 802.11 b/g/n IEEE 802.3 10Base-T Ethernet IEEE 802.3u 100Base-TX Fast Ethernet
Strømforbrug	:	2 Watts
Strømforsyning	:	9 to 48VDC redundant input



SPECIFICATIONS

Vekt	:	ca 1 KG
Dimensioner	:	26 x 95 x 75 mm

