

Fjernlesning over Ethernet med 24 inngange. 4 digital inngang, 50. 6 x analog inngang. RS485. ModbusRTU til Modbus TCP. SNMP.

FEATURES

- Datalogger med flere innganger for opptil 70 000 logger
- 10/100 Mbit Ethernet
- Passordbeskyttet, nettbasert konfigurasjon og kontroll
- 4 digitale innganger, kompatible med 50-pulsgrensesnitt
- 6 analoge innganger med 0/10V og 0/20mA
- MODBUS RTU-grensesnitt for opptil 24 sensorer (registre)
- Opptil 24 kanaler for overvåking
- Opptil 24 uavhengige alarmer
- SNMP v.2-støtte - SNMP Trap - alarmvarsler
- HTTP- og SNMP-portendring - HTTP API-kommandoer
- Periodisk HTTP-publisering av XML/JSON-statusfiler til klient-server-systemer
- MODBUS TCP/IP-støtte
- Dynamisk DNS med støtte for DynDNS, No-IP og DNS-O-Matic
- Støtte for NTP-protokoll
- Forsyningsspenning: 10 til 28 V DC



SPECIFICATIONS

Driftstemperatur	:	-20° - +55°C
Hukommelse	:	Internal FLASH memory Settings segment endurance: 100 000 cycles (Every setting change is a memory cycle). Data logger segment endurance: 100 000 cycles of 70000 records. Update segment endurance: 100 000 cycles (updates).
Indgang	:	Isolation: Isolated (1000VDC) Mode: OPEN/CLOSED ("Dry contact") or COUNTER (S0-pulse interface outputs) Maximum input voltage: +5.5VDC Sampling rate: 1mS Digital filtering time interval: 5 to 60000mS
Indgang	:	Isolation: Isolated (1000VDC) Type: Single ended Resolution: 10 bits Mode: Voltage or current loop Input Range: 0/10V or 0/20mA Accuracy: ±1% Sampling Rate: 600mS per channel (averaged value of 100 samples) Input Impedance: 1 mega-ohm (min.)
Luftfugtighed	:	10 to 80% (non-condensing)
Strømforbrug	:	220 mA @ 12 VDC (without RS-485 powering)
Strømforsyning	:	10 til 32V DC
Vekt	:	200g
Dimensioner	:	145 x 90 x 40

