

Embedded fanless system med Celeron® CPU N3160 (1,6 Ghz / 4core), opptil 8 GB, mSATA og SATA SSD eller HDD

FEATURES

Kostnadseffektiv med fanless og cableless design
Intel® Celeron®-prosessor N3160 (1,6 GHz / 4-kjerne)

2 x RS-232/422/485 porter

4 x USB-porter

2 x isolerte 10/100/1000 Mbps Ethernet-porter

1 x PoE PD kompatibel med IEEE 802.3at standard LAN 1

1 x DIO-port

2 x PCI Express Mini-kortspor (3G / GPRS og Wi-Fi Fi)

1 x mSATA & amp; SATA SSD (eller HDD)

12 til 24 VDC

Vekt: 1,50 KG

Dimensjoner: 48 x 110 x 155 mm

DIN skinne og veggmontering

OS-støtte: Windows® 7 Embedded, Windows® 8

Embedded, Windows® 8, Windows® 10, Linux-støttepakke



SPECIFICATIONS

CPU	:	intel® Celeron® processor N3160 (1.6 GHz/4-core)
USB	:	2 x USB 3.0 2 x USB 2.0
Driftstemperatur	:	-20°C to +60°C
Farve	:	Sølv
BIOS	:	AMI UEFI BIOS
Beskyttelse	:	DC version OVP, reverse protection
Chok/Vibration	:	2 Gms (5 to 500Hz, amplitude 0.35 mm; operation/storage/ transport
Harddisk	:	1 x mSATA 1 x SATA SSD (or HDD)
Hukommelse	:	1 x DDR3L-1600 SO-DIMM, op til 8GB
Luftfugtighed	:	10% to 95%
Montering	:	Din skinne og væg montering
Netværk	:	2 x 10/100/1000 Mbps Ethernet (Intel® i211AT) 1 x PoE PD compliant with IEEE 802.3at standard through LAN 1



SPECIFICATIONS

Porte	:	2 x RS-232/422/485 (COM 1/2) with DB9, 2 x USB 3.0, 2 x USB 2.0, 2 x 10/100/1000 Mbps Ethernet, DC terminal block: 12 to 24V DC-In, VGA (DB15 connector),
Software	:	AXView 2.0 Intelligent Remote Management Solution for IoT
Strømforsyning	:	DC terminal block: 12 to 24V DC-In PoE: IEEE 802.3at
Trådløs	:	1 x Full-size PCI Express Mini Card slot 1 x Full-size PCI Express Mini Card slot with mSATA 1 x SIM card socket 3 x Antenna
Vekt	:	1.50 KG
Dimensioner	:	48 x 110 x 155 mm

