

12-Port Industrial PoE + Gigabit Unmanaged Switch FEATURES

- 8 x 10/100 / 1000Tx RJ45 (30W / port)
- 2 x 10/100 / 1000Tx RJ45
- 2 x 100/1000 SFP-porter
- Auto MDI / MDI-X Funksjon
- Arkiv for lagring og viderekobling
- 24Gbps Back-Plane (Switching Fabric)
- 8K MAC-adressetabell
- 9.6Kbytes Jumbo Frame
- Overspenningsvern: 2000 VDC
- ESD-beskyttelse: 6000 VDC > UL klasse I, divisjon 2-sertifisert
- Strømforsyning: 48 ~ 55VDC
- Innebygd reléutgang for strømrbrudd
- IP30 Robust Metal Case Design
- DIN-skinne og veggmontering
- Driftstemperatur STD: -10 ° til 70 ° C



SPECIFICATIONS

Driftstemperatur	:	STD: -10° to 70°C
Buffer	:	7,926pps (default)
Chok/Vibration	:	IEC60068-2-32, IEC60068-2-27
Ethernet	:	10*10/100/1000Tx RJ45 (w/8*PSE: 30W/Port)
Fiber	:	2 x 10/100/1000 SFP Slot
Forbindelse	:	1 removable 6-contact terminal block
Luftfugtighed	:	5% to 95%, (non-condensing)
Montering	:	DIN-skinne og væg montering
Protokol	:	CSMA/CD
Standarder	:	IEEE 802.3 10BaseTx Ethernet IEEE 802.3u 100BaseTx Fast Ethernet IEEE 802.3ab 1000BaseTx IEEE 802.3z Gigabit Fiber IEEE 802.3at PoE+
Strømforbrug	:	10 Watts Full load w/PoE 215W@48V / 255W@51~55V
Strømforsyning	:	48-55VDC



**DANBIT**

ANR-LNP-1202G-SFP

SPECIFICATIONS



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.