

26-ports industriell gigabit ustyrt bryter, IP40, 1U, 19 "Rackmontert

FEATURES

- 24 x 10/100 / 1000Tx RJ45
- 2 x Gigabit Combo Ports
- 2 x 10/100 / 1000Tx RJ45
- 2 x 100/1000 SFP Slots
- Auto MDI / MDI-X Funksjon
- Store-og-videresende byttearkitektur
- 8K MAC-adressetabell
- 9.6Kbytes Jumbo-ramme
- Overspenningsvern: 2000 VDC
- ESD-beskyttelse: 6000 VDC
- Redundant Power Input Design: 90 ~ 264VAC
- 1 x Innebygd reléutgang for strømbrudd
- IP40 Robust Metal Case Design
- 1U 19 "Rackmontert Design Support
- Driftstemperatur: -10 ° til 70 ° C



SPECIFICATIONS

Driftstemperatur	:	STD: -10° to 70° C
Approval	:	EMI, EMS, FCC Part 15 Subpart B Class A, CE EN 55022 Class A
Buffer	:	4Mbps (buffer)
Chok/Vibration	:	IEC60068-2-27, IEC60068-2-6
I/O	:	26 x RJ45 10/100/1000Tx, 2 x 100/1000 SFP Slots
Luftfugtighed	:	5 to 95%, (non-condensing)
Montering	:	1U 19" Rackmount
Netværk	:	10Base Tx: UTP/STP Cat. 3,5 100Base Tx: UTP/STP Cat. 5 1000Base Tx: UTP/STP Cat.5/5e/6
Protokol	:	CSMA/CD
Standarder	:	IEEE 802.3 10BaseT Ethernet IEEE 802.3u 100BaseTX Fast Ethernet IEEE 802.3ab 1000BaseT IEEE 802.3z 1000Base-X Gigabit Fiber
Strømforbrug	:	24Watt
Strømforsyning	:	90-264VAC/47-63Hz



**DANBIT**

ANR-LNX-2602G-SFP

SPECIFICATIONS



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.