

ANR-LNP-1002G-SFP

10-port industriell ustyrt bryter med 2 SFP-porter og 8 RJ45-porter.

## FEATURES

- 8 x 10/100/1000Tx RJ45 IEEE 802.3at PoE+
- 2 x 100/1000 SFP porte
- Auto MDI/MDI-X Funktion
- Store-and-Forward Switching Architecture
- 20Gbps Back-Plane (Switching Fabric)
- 8K MAC Address Table
- 9.6Kbytes Jumbo Frame
- Surge Protection: 2,000 VDC
- ESD Protection: 6,000 VDC
- UL Class I, Division 2 Certified
- Strømforsyning: 48~55VDC
- Indbygget relæ Output for Power Failure
- IP30 Rugged Metal Case Design
- DIN-Skinne og Væg montering
- Driftstemperatur STD: -10° to 70° C



Danbit A/S Schous plass 1 Oslo, N-0552  
Norway



67 104 460



salg@danbit.dk

## SPECIFICATIONS

|                  |   |                                                                                                                                         |
|------------------|---|-----------------------------------------------------------------------------------------------------------------------------------------|
| Driftstemperatur | : | STD: -10° to 70°C                                                                                                                       |
| Ethernet         | : | 8 x RJ45 Ports w/10/100/1000Tx (PSE 30W/Port)                                                                                           |
| Fiber            | : | 2 x 100/1000 SFP Slot                                                                                                                   |
| Luftfugtighed    | : | 5 to 95%, (non-condensing)                                                                                                              |
| Montering        | : | DIN-skinne og væg montering                                                                                                             |
| Netværk          | : | 10Base Tx: 2-pair UTP/STP Cat. 3,4,5 100Base Tx: 2-pair UTP/STP Cat. 5<br>1000Base Tx: 2-pair UTP/STP Cat. 5/5E                         |
| Protokol         | : | CSMA/CD                                                                                                                                 |
| Standarder       | : | IEEE 802.3 10BaseTx Ethernet IEEE 802.3u 100BaseTx Fast Ethernet IEEE<br>802.3ab 1000BaseTx IEEE 802.3z Gigabit Fiber IEEE 802.3at PoE+ |
| Strømforbrug     | : | 210 Watts @ 48V 250 Watts @ 51-55V (Full Load w/ PoE)                                                                                   |
| Strømforsyning   | : | 48~55VDC, Redundant Input                                                                                                               |
| Dimensioner      | : | 46 x 99 x 142 mm (W*D*H)                                                                                                                |

