

E-MARK, fanless Embedded PC, med 8x RJ45 PoE + - porter, DIO, CAN-buss og RAID GEN 8/9

FEATURES

- NO 50155 Sertifikat (jernbane) og E-merket Embedded PC
- Støtter Intel® 8th / 9th Gen Core™ I7 / I5 / I3 LGA1151 Socket-type CPU
- Opptil 64 GB DDR4 2666/2400 SDRAM (To Sodimm Slots)
- 4 x 802.3at Gigabit Poe + Porter via RJ45-kontakt (må spesifiseres etter bestilling)
- Isolert CAN Bus for kjøretøyskommunikasjon
- 4 lm isolert DI og 4-CH isolert 2 x SATA-porter med en hot-swapbar HDD Hill Supports Raid 0/1
- 2 x M.2 Slot
- 3 x Mini PCIe i full størrelse
- 8 ~ 35VDC Input, Tenningskontroll



SPECIFICATIONS

CPU	:	Supporting Intel® 8th/ 9th-Gen CPU (LGA1151 socket, 65W/ 35W TDP) - Intel® Core™ i7-8700/ i7-8700T/ i7-9700E/ i7-9700TE - Intel® Core™ i5-8500/ i5-8500T/ i5-9500E/ i5-9500TE - Intel® Core™ i3-8100/ i3-8100T/ i3-9100E/ i3-9100TE
Chipset	:	Intel® Q370 Platform Controller Hub
Digital I/O	:	4x isolated DI and 4x isolated DO
USB	:	4x USB 3.1 Gen2 (10 Gbps) ports 4x USB 3.1 Gen1 (5 Gbps) ports
Driftstemperatur	:	-40°C ~ 70°C For sub-zero operating temperature, a wide temperature HDD/SSD is required, For i7-8700 running at 65W mode, the highest operating temperature shall be limited to 50°C
Approval	:	E-Mark (Nuvo-7108VTC) CE/FCC Class A, according to EN 55022 & EN 55024
Chok/Vibration	:	Operating, MIL-STD-810G, Method 514.6, Category 4 Shock Operating, MIL-STD-810G, Method 516.6, Procedure I, Table 516.6-II
Forsyning	:	1x 3-pin pluggable terminal block for 8~35V DC input (IGN/ GND/ V+) Remote Ctrl. & Status Output 1x 3-pin pluggable terminal block for remote control and PWR LED output
Grafik	:	Integrated Intel® HD Graphics 630, 1x VGA connector, supporting 1920 x 1200 resolution 1x DVI-D connector, supporting 1920 x 1200 resolution 1x DisplayPort connector, supporting 4096 x 2304 resolution
Hukommelse	:	Up to 64 GB DDR4 2666/ 2400 SDRAM (two SODIMM slots)
Interface	:	1x isolated CAN 2.0 port
Luftfugtighed	:	10%~90% , non-condensing



SPECIFICATIONS

Montering	:	patented damping bracket (standard) or optional DIN-rail mounting
Porte	:	2x software-programmable RS-232/422/485 ports (COM1/ COM2) 2x RS-232 ports (COM3/ COM4)
Udgange	:	1x VGA, supporting 1920 x 1200, 1x DVI-D connector 1920 x 1200 resolution 1x DisplayPort connector 4096 x 2304 resolution
Vekt	:	3.3 Kg
Dimensioner	:	240 mm (W) x 225 mm (D) x 84 mm (H)

