

Wifi-bro, Wifi Uplink, Ethernet/UART til Wi-Fi-omformer. 3 forskjellige grensesnitt Wifi, Ethernet og UART RS232/485. Roaming

FEATURES

- Wifi Uplink eller Ethernet WAN-tilkobling
- 1 x LAN-port
- 1 x RS232 / RS485 for Modbus RTU
- 1 x digital inngang / 1 x digital utgang
- Roaming - feltstyrke kontrollert
- IEEE 802.11a/b/g/n/ac Wi-Fi
- Forsyningsspenning: 9 til 48 VDC
- DIN-skinne
- Driftstemperatur -20°C til +60°C
- Mål: 131 x 108 x 31 mm



SPECIFICATIONS

Driftstemperatur	:	-20 °C to 60 °C
Afstand	:	Op to 50 meters
Antenne	:	5 dBi 2.4/5 GHz
Forbindelse	:	Max. 10 Clients (AP mode)
Indgang	:	1 x DI ("Logic 0": 0~3V, "Logic 1": 3.3V~30V)
Input	:	+9 to 48
Kanaler	:	2.4GHz 1~11 / 5GHz 36/40/44/48/149/153/157/161/165
Montering	:	DIN-Rail
Porte	:	1 x RJ45 / 1 x RJ10
Protokol	:	WEP / WPA / WPA2 / WPA-PSK / WPA2-PSK
Standarder	:	IEEE 802.11a/b/g/n/ac
Udgange	:	1 x DO (Relay Mode, up to 30V / 1A)



**DANBIT**

WLAN-AP-CNV

SPECIFICATIONS



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.