

Intel® niende / åttende -Gen Core™ i7 / i5 / i3 Kompakt Vifteløs PC med 2x GbE og 4x COM-porter FEATURES

- Compact 255 x 173 x 76 mm footprint
- Intel® 9th/ 8th-Gen Core™ 35W LGA1151 CPU
- Rugged, -25°C to 60°C fanless operation
- 2x GbE and 4x USB3.0
- 2x RS-232/422/485 and 2x RS-232 ports
- VGA + DVI dual display outputs
- Supports 1x M.2 2280 SSD (SATA signal)
- Supports 1x 3.5" or 2.5" SATA HDD/ SSD



SPECIFICATIONS

CPU	:	Supporting Intel® 8th/ 9th-Gen Core™ CPU (LGA1151 socket) - Intel® Core™ i7-8700*/ i7-8700T/ i7-9700E*/ i7-9700TE - Intel® Core™ i5-8500*/ i5-8500T/ i5-9500E*/ i5-9500TE - Intel® Core™ i3-8100*/ i3-8100T/ i3-9100E*/ i3-9100TE
Chipset	:	Intel® H310 platform controller hub
Digital I/O	:	OPTIONAL ! Contact sales
USB	:	4x USB 3.1 Gen1 (5 Gbps) ports
Driftstemperatur	:	-25°C ~ 60°C For sub-zero operating temperature, a wide temperature HDD or Solid State Disk (SSD) is required.
Annen	:	Remote Ctrl. & LED Output 1x 10-pin (2x5) pin header for remote on/off control and status LED output
Approval	:	CE/FCC Class A, according to EN 55032 & EN 55024
Chok/Vibration	:	Vibration Operating, MIL-STD-810G, Method 514.6, Category 4 Shock Operating, MIL-STD-810G, Method 516.6, Procedure I, Table 516.6-II
Ethernet	:	2x Gigabit Ethernet ports by I219 and I210
Grafik	:	Integrated Intel® UHD Graphics 630
Hukommelse	:	Up to 32 GB DDR4 2666/ 2400 SDRAM (one SODIMM slot)
Luftfugtighed	:	10%~ 90% , non-condensing



SPECIFICATIONS

Montering	:	Wall Mount or Optional DIN Rail
OS SUPPORT	:	WIN 7 (32/64-Bit) WIN 8/8.1, WIN 10, WIN 10 IOT
Porte	:	2x software-programmable RS-232/ 422/ 485 ports (COM1/ COM2) 2x RS-232 ports (COM3/ COM4)
Strømforsyning	:	1x 3-pin pluggable terminal block for 8~35VDC DC input
Udgange	:	1x VGA connector, supporting 1920 x 1200 resolution 1x DVI-D connector, supporting 1920 x 1200 resolution
Vekt	:	2.68Kg
Dimensioner	:	255mm (W) x 173 mm (D) x 76 mm (H)

