

Kompakt 400VA UPS med 3 X Schuko utganger FEATURES

- Singel-fasen
- Linje-Interaktiv
- Green UPS-bypass-teknologi
- 230 ± 10%
- Schukokontakt
- 400VA
- overbelastnings
- 3 x schuko ut
- Kjøretid ved 60W 28min
- Kjøretid ved 90 W 16 min
- forseglede bly-syre-batteri



SPECIFICATIONS

USB	:	1 port HID compliant
Driftstemperatur	:	0 ~ 40 degrees
Alarm	:	Power On, Line Mode, Battery Mode, Bypass Mode, Low Battery, Overload, UPS Fault
Approval	:	CE
Beskyttelse	:	Surge suppression 125 Joules, EMI/RFI ,
Effekt	:	250Watt , 400VA
Ethernet	:	yes, up to 1GB
Forsyning	:	230 ± 10%
Frekvens	:	50 ± 1% 60 ± 1%
LED	:	Power On, Line Mode, Battery Mode, Bypass Mode, Low Battery, Overload, UPS Fault
Overvågning	:	Software for Windows, MAC, Linux
Software	:	PowerPanel® Personal (Recommended)



**DANBIT**

UPS400

SPECIFICATIONS

Dimensioner : 84 x 174 x 280 mm



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.