

MODBUS TCP Server, RTU slave til CANopen Master, 3
i 1 Gateway, 1 x RJ45, 1 x COM, 1 x CAN, -25 - +75°C,
10 - 30 VDC

FEATURES

Ethernet Gateway for CANopen nettverk og Modbus
RTU

1 x RJ45 10/100 Mbps

Protokoll: Modbus TCP Server

1 x RS232 / RS485 port (ikke isolert)

Modbus RTU slave

Baud rate: 1200-115200

1 x CAN port

CANopen

CAN Baud rate: 10 K - 1M

Innebygd 120 ohm terminering

Dimensjoner: 122 x 72 x 33 mm

Forsyningsspenning : 10 - 30VDC, 2,5Watt

Driftstemperatur: -25 - + 75 ° C

DIN brakett



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

SPECIFICATIONS

Driftstemperatur	:	-25 - +75°C
Forsyning	:	10 - 30VDC, 2.5Watt
Mål og vægt	:	122 x 72 x 33 mm
Netværk	:	1 x RJ45 10/100Mbit
Porte	:	1 x RS232 og 1 x RS485 (en kan vælges)
Porte	:	1 x CAN bus - CiA 301 v4.02
Skærm	:	5 cifret 7-segment LED display
Tilslutning	:	Op til 10 CANopen slave-moduler, 120 kommandoer SDO/PDO

