

IPP10.1P65F2

10,1" panel-PC full IP66/IP69K celeron 2930 4 GB
RAM, 32 GB MLC SSD

FEATURES

10,1" rustfritt stål panel PC
350 cd/m²
Intel Celeron N2930 1,83 GHz innebygd prosessor
8 GB innebygd DDR3L SDRAM maks. 8 GB totalt
Flat frontramme Design
klasse 304 rustfritt stålhus (klasse 316 er alternativ)
IP66 / IP69K klassifisert med M12-kontakt
Støtt resistiv berøring, forventet kapasitiv berøring og Glass Touch
av/på-knapp på siden Kant for hygienisk rengjøring
Støtte Ergonomisk allsidig montering: Åkmontering / plassbesparende VESA 75 x 75 mm montering
TILVALG HØY LYSSTYRKE 1000cd/m²



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

SPECIFICATIONS

CPU	:	Celeron N2930 2M cache, 1.83GHz
USB	:	1 x M12 8 pin USB 2.0 waterproff cover and chain
Driftstemperatur	:	0~50oC
Antal farver	:	16.7M
Approval	:	CE/FCC class A
Ethernet	:	1 x M12 8 pin for LAN with waterproff cover and chain
Forsyning	:	9~36Vdc , power consupion 18Watt
Hukommelse	:	Onboards 4GB DDR3L SDRAM, Max 8GB(option)
LCD	:	10.1"TFT 1280x800
Montering	:	VESA mount 75x75, Option Yoke Mount
OS SUPPORT	:	Windows embedded 7, 8.1 and windows 10 IoT ENT LTSB
Porte	:	1 x M12 8 pin COM1, RS232/422/485 default RS232 with waterproff cover and Chain



**DANBIT**

IPP10.1IP65F2

SPECIFICATIONS

Touch	:	Resistive Touch USB, light transmission 80%. Option GLASS and Projected touch
Dimensioner	:	300x220x53mm



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.