

PIR-bevegelsessensor, temperatur og lys-nivå setting,
reléutgang M485, Modbus RTU, DCON, 10 - 30VDC.
innendørs

FEATURES

- Bevegelsessensoren lys deteksjon, temperaturføler for energistyring
- Kobler energistyring, lokal-lysstyring via RS485 port
- Med kraftig innebygget relé for enkel lysaktivering 250VAC (1500 Watt T8)
- 360 ° bevegelsesdeteksjon - opp til 8 meter i diameter og 4 m høyde
- Tidsforsinkelse / følsomhet er justerbar
- temperatursensor, - måling av romtemperaturen eller brannalarm
- Relé utgang for å slå på lyset via PIR / lys-styrke og temperaturfølere
- RS485 2-tråds kommunikasjonsbuss
- DCON og Modbus RTU protokoller
- loft montering
- Forsyningsspenning: 10 - 30VDC ca. 2W
- Mål: Ø121 x 52 mm
- IP20



SPECIFICATIONS

Serial	:	1x RS-485 DCON, Modbus RTU
Driftstemperatur	:	0 to +35°C
Annen	:	Hardware: 8-step Switch-selectable (seconds): 6, 16, 33, 66, 131, 262, 524, 1049 Software: 16-step (seconds): 2, 4, 6, 8, 16, 33, 49, 66, 131, 262, 393, 524, 1049, 2097, 3146, 4194
IP-Tæthed	:	IP20
Luftfugtighed	:	10 to 90% RH, Non-condensing
Lysstyrke	:	Hardware: 2 mode (Dawn and dust) / Software: 5-step
Montering	:	Ceiling mounting
Relæ	:	1x Power Relay, Form C; NO: 10 A @ 250 VAC NC: 6 A @ 250 VAC
Strømforsyning	:	10 to 30 VDC (1.3 W)
Temperatur	:	Measurement Range: -25 ~ +100°C Accuracy: ±2°C
Range	:	Distance: 4 meters Max. 360°; Diameter 8 meters Max.
Dimensioner	:	121 mm x 52 mm

