

MON22-PW-T-DIMM

22" 16:9 Industriell skjerm, Med resistiv berøring,
VGA, HDMI, Ekstern dimming for å justere lysstyrken.
Alternativ: 1000Nits

FEATURES

22" (16:9)
Oppløsning: 1920x1080
Innganger: VGA, HDMI
Resistive Touch (Alternativ: Projective Glass, SAW)
USB. (alternativ: RS232)
OSD
Driftstemperatur: 0 ~ 50 °C
Forsyningsspenning: 12Vdc
Alternativ: 1000 nits



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

SPECIFICATIONS

Driftstemperatur	:	0~50C
Annen	:	External DIMM knob for adjusting from 0 to 100%
Antal farver	:	16.7M (8bit/color)
Betragningsvinkel	:	-89~89(H) ; -89~89(V)
Forsyning	:	12Vdc (2.5) with external AC-DC adapter (100~240Vac)
Indgang	:	1xVGA, 1xHDMI
Kontrast	:	3000:1 (typical)
Lyd	:	OPTION! Audio line in (3.5mm) + 2xSpeaker
Lysstyrke	:	250 cd/m(typical)
Skærm	:	476,64 (H) x 269.11 (V)
Skærm	:	22" 16:9
Strømforbrug	:	Typical 40W normal operation



**DANBIT**

MON22-PW-T-DIMM

SPECIFICATIONS



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.