

4G-modul LTE RS232 RS485 Modbus RTU TCP LTE-FDD WCDMA GSM trådløst transparent transceivermodem

FEATURES

- AT-kommandoer kommunikasjon
- Bandwidth 1.4/3/5/10/15/20MHz
- LTE-FDD: B1 / B3 / B7 / B8 / B20 / B28A
- WCDMA: B1 / B8
- GSM: B3 / B8
- inngang DC 8V-28V
- arbeidstemperatur -30 °C -70 °C
- dimensjoner 82 x 84 x 24 mm
- Max oppstrøms hastigheten 50 Mbps
- Max nedstrøms hastighet 150Mbps
- RS485 / RS232



SPECIFICATIONS

Antenne	:	SMA
Baudrate	:	Max 921600bps□default 115200bps
Dimensioner	:	82×84×24mm
Driftstemperatur	:	-30°C- +70°C
Frekvens	:	1.4/3/5/10/15/20MHz
Porte	:	RS485 / RS232
Protokol	:	TCP/UDP/PPP/FTP/HTTP/NTP/PING/QMI/NITZ/CMUX/HTTP S/SMTP/MMS/FTPS/ SMTPS/SSL/FILE
Strømforbrug	:	20mA idle
Strømforsyning	:	DC 8V~28V