

## 2 Port Serial Port Server - Seriell Device Server, RS232 / RS422 / RS485 Port over Ethernet. 2 x RJ45, 2 x DB9 Han, 12 - 48VDC

### FEATURES

2 COM Porter over Ethernet, Internett  
hver COM-port kan være RS232 eller RS422 eller RS485  
RS232 PIN 1 - 8: DCD, RXD, TXD, DTR, GND, DSR, RTS, CTS  
RS422 / RS485 4-W: PIN 1 - 5: TXD +, TXD, RXD +, RXD, GND  
RS485 2-W: PIN 3 - 5: Data, data +, GND  
Baud Rate: 50 BPS - 921kbps  
databiter: 5, 6, 7, 8  
Paritet: 1, 1.5, 2  
Stoppbit: Odd, Even, None, Space, Mark  
2 x RJ45 10/100Mbit  
Alarm: Reléutgang  
Supply Spenning: 12 - 48VDC 6.5watt  
Webadministrasjon  
IP-versjon: IPv4 / IPv6. TCP-server, TCP-klient, UDP-klient  
Virtual Com  
Pair-tilkobling  
Supporter: XP til Win10, Server 2003, 2008, 2012  
Mål: 135 x 88 x 32 mm  
DIN brakett

