

KAM-2M-STEEL

2 megapiksler bullet IP-kamera, Anti-korrosjon,
Stålhus, IP68 / IP69, -40°C - +65°C

FEATURES

- 316L hus i rustfritt stål
- Anti-korrosjon
- NEMA-4X, IP68/ IP69
- 2 megapiksler IR Bullet IP-kamera
- H.264+/ H.264/ M-JPEG-komprimering
- Smart fokussystem for fjernfokusjustering
- Digital støyreduksjon
- Strøm over Ethernet
- Dag Natt Manuell Switch Tidskontroll
- Driftstemperatur -40°C~65°C med varmeapparat
- IR LED Innebygd 45M/spenn
- IR Cut Filter Mekanisme
- Sikkerhetskopiering av mikro SD-kort
- 2-veis lyd
- Støtte iPhone/Android/Mac
- SDK for programvareintegrasjon
- Gratis pakke 36-kanals opptaksprogramvare



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

SPECIFICATIONS

Driftstemperatur	:	-40°C~70°C
I/O	:	DIx1, DOx1, RJ45, DC JACK, BNC Output, Micro SD card slot built-in (optional)
IP-Tæthed	:	IP68, IP69
Linse	:	2.8-12mm 4.2X Bulid-in Zoom Lens @ F1.4
Lyd	:	Audio Format G.711 (64K) / G.726 (32K, 24K) Audio Input: External line in Output: External line out Support 2 way audio
Lysfølsomhed	:	Color 0.005 lux, (AGC ON)
Opløsning	:	1920x1080@30fps 1280x720@30fps 640x360@30fps (2M)
PoE	:	Max:8.16W(IR ON), 3.36W(IR OFF)
Protokol	:	IPv6, IPv4, HTTP, HTTPS, SNMP, SSL, TLS, DNS, ICMP, IGMP, ARP, SNTP, QoS/DSCP, IEEE 802.1X, RTSP/RTP/RTCP, TCP/IP, UDP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP, UPnP, SAMBA, Bonjour, Google Drive, Dropbox, ONVIF Profiles
Sensor	:	1/2.8" Sony True WDR Starvis CMOS Sensor
Strømforbrug	:	DC 12 Max:7.53W(IR ON), 2.28W(IR OFF)
Vekt	:	2,25Kg



**DANBIT**

KAM-2M-STEEL

SPECIFICATIONS



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.