

17" panel-PC, stål foran, Gen. 12/13/14, i3/i5/i7/i9.
1xPCIe (x16) utvidelse, 4xCOM, Resistive Touch, USB,
8 DIO

FEATURES

17" TFT LCD (LED) oppløsning 5:4 1280x1024 FLAT
PANEL
SUS304 rustfritt stål
Intel® 14./13./12. generasjon.
Core™ i9/i7/i5/i3 Pentium® Celeron® opptil 35W
Resistiv berøring. (på forespørsel: Kapasitiv
/projisert)
6 x USB
1 x DP
1 x HDMI
4 COM-porter
DDR5 opptil 64 GB
2 x 2,5" SATA III SSD
1 x PCIe (X16) spor ½ lengde, 1 x M.2 2230-E, 1 x
M.2 3042-B, 1 x M.2 3042-B, 1 x MXM Type A
2 x GBE LAN, støtte Wake-on-LAN, PXE
TBD
OS-støtte Windows 10 IoT LTSC 2021, Windows 11
IoT Enterprise GAC Ubuntu 22.04 (kjerne: 5.15)
Frontpanel IP65 beskyttelse
-20°C~70°C, (med bred temperatur SSD)
Avtakbar harddisk / SSD-stasjonsplass
VESA 75 , Panelmontering
DC In 12/24V
CE / FCC



SPECIFICATIONS

CPU	:	Core i7-7700T, i5-7500T, i3-7101TE, Cel. G3930TE
Chipset	:	Intel Q170/H110
USB	:	4xUSB 3.0, 4x USB2.0
Driftstemperatur	:	Operating Temp. HDD: 0°C~45°C (32°F~113°F) (Ambient with airflow) SSD: 0°C~50°C (32°F~122°F)
LPT	:	1 x Parallel port (SSP/EPP/ECP)
Antenne	:	2 x antenne holes (no antennea incl.)
Approval	:	CE/FCC
Ethernet	:	2 x RJ45 ports LAN 1: Intel® PHY I219LM (10/100/1000 Mbps) LAN 2: Intel® LAN 210AT (10/100/1000 Mbps) Support Wake-On-LAN, PXE
Hukommelse	:	3xDDR4 2133MHz So-DIMM (max 32GB)
IP-Tæthed	:	IP65 FRONT ONLY
LCD	:	17" TFT LCD (LED) 5:4 SXGA
Lyd	:	1 x Line In / 1 x Line Out / 1 x Mic In



SPECIFICATIONS

Opløsning	:	SXGA 1280x1024
OS SUPPORT	:	Windows 10 IoT enterprise (64 bit)
Porte	:	4 COM ports COM 1 for RS-232/422/485 COM 2/COM 3/COM 4 for RS-232 COM 1/COM 2/COM 4 support +5V/+12V/RI selectable
Touch	:	Resistive touch. (option: Capacitive /projected)
Udgange	:	2 x DVI-D
Udvidelser	:	1 x PCIe (x16)
Watchdog	:	1~255 sec. timer selectable
Vekt	:	9.1 KG
Dimensioner	:	436x368x102,55mm (WxHxD)

