

## Dobbel elbillader med betalingsterminal, elavgiftsmelding med CVR-nummer. i Danmark FEATURES

- Universelt ladestativ for elbiler for alle elbiler
- La to elbiler lade samtidig
- Smart design
- Dynamisk styring av lading
- Grensesnittprotokoll: OCPP 1.6
- Betaling for parkering og lading med betalingskort
- Månedlige avgifter påløper
- AC-inngang 230-400 VAC +/- 10 (2 eller 3 fase)
- Total effekt 2 x 22kW / 2 x 32A Max (belastningsdeling)
- Betaling: Betalingskort, Google Pay, Apple Pay (alternativ: MobilePay)
- Kommunikasjon: 4G
- IP-grad: IP55
- Driftstemperatur: -25 C° til 55 C°
- Mål: 520 x 360 x 260 mm
- Ladekabel følger ikke med. Brukeren bruker kabelen som følger med bilen.



## SPECIFICATIONS

|                  |   |                                                                                                                                                                              |
|------------------|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Driftstemperatur | : | (-25°C) to (+55°C)                                                                                                                                                           |
| Annen            | : | Supported Payment: Debit & Credit Cards, Swipe, contact, contactless, EMV chip cards Schemes Mobile & NFC Payments Google Pay, Apple Pay, MobilePay Bluecode, Swish and more |
| Beskyttelse      | : | Electronic RCD 30mA Type A, Electronic 6mA DC Fault current detection                                                                                                        |
| Indgang          | : | IEC-62196 Type 1 connector                                                                                                                                                   |
| IP-Tæthed        | : | IP55                                                                                                                                                                         |
| Maks. effekt     | : | 44kW / 64Amax                                                                                                                                                                |
| Protokol         | : | Bluetooth, Wi-Fi, GSM/GPRS                                                                                                                                                   |
| Strømforsyning   | : | 230-400 VAC +/-10 (3P + N + PE)                                                                                                                                              |
| Dimensioner      | : | 450x300x180mm                                                                                                                                                                |

