

Vifteløs innebygd PC med 11. generasjons Intel® i3 CPU, 9~36 VDC, -20 ~ 60 °C, 4x COM, 3x LAN, 4x USB DIN mount

FEATURES

- 11. generasjons Intel® i3-prosessor (valgfritt: i5, i7)
- 2 x 260-pinners DDR4 SO-DIMM (maks. 64 GB)
- 1 x M.2 M-nøkkel, 1 x 2,5" harddisk/SSD
- 16 x I/O
- 4 x KOM
- 3 x LAN (2 x PoE)
- 4 x USB 3.1
- TPM 2.0
- Sikker oppstart
- Fjernstyrt strømforsyning
- Videoutgang: DVI-D, HDMI, DP
- Montering: Veggmontering (alternativ: DIN-skinne eller VESA)
- Strøminngang: 9~36 VDC
- Dimensjon: 210x180x70mm (BxDxH)
- Driftstemperatur -20 ~ 60 °C



SPECIFICATIONS

CPU	:	Soldered onboard Intel® i7/ i5/ i3 Processor (Default: i3 CPU Tiger Lake-U)
Chipset	:	soc
Digital I/O	:	8 x DI, 8 x DO w/ 1.5KV isolation
USB	:	4 x USB 3.2 Gen2 (2 w/ independent full speed), 1 x USB 2.0 onboard for encryption dongle (Type A)
Chok/Vibration	:	5~500Hz 3 Grms X,Y,Z axis w/ SSD, 40G peak acceleration (11 m sec. duration), operation w/ SSD
Harddisk	:	1 x M.2 M-Key 2242/2280, 1 x 2.5" HDD/SSD
Hukommelse	:	2 x 260-pin DDR4 SO-DIMM socket, supporting 3200MHz SDRAM up to 64GB
Input	:	DC 9 ~ 36V (3-pin terminal block: V+, V-, GND)
Montering	:	Wall-mount (standard) DIN-rail or VESA mount (optional w/ CTOS bracket)
Netværk	:	2 x RJ-45 ports for GbE LAN (PoE complies with IEEE802.3af), 1 x RJ-45 ports for 2.5 GbE LAN (iAMT support w/ i5/i7 skus)
Porte	:	2 x RS232 (DB-9 male connectors), 2 x RS232(Default) / 422/ 485 (RI/ 5V/ 12V) (DB-9 male connector/ Switch via BIOS)
Udvidelser	:	1 x full mPCIe slot, 1 x M.2 B-Key 2242/3042/3052



**DANBIT**

EPC-GEN11-I3

SPECIFICATIONS

Vekt	:	3.7kg
Dimensioner	:	210 x 180 x 70 mm



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.