

IPP12-IX-1000N

12.1 "Industriell PC, I3 / I5 CPU, USB, RS232,
Touch, 450/500/1000 Nits Versjoner, 9 ~ 36VDC
Supply Mange alternativer!

FEATURES

- 12,1" TFT
- CPU Gen.6 i3-standard (i5-alternativ)
med eller uten Touch resistiv, projisert kapasitiv
- 7H anti-ripe overflate
- 1 x 260-pinners SO-DIMM DDR4 2100Mhz maks. 16 GB
- 2 x USB 3.0
- 1x 2½" SSD SATA
- 1 x Mini PCIe-spor i full størrelse
- 1xDB9 RS232 / 422/485, COM1, 1x RS-232 DB9 COM 2
- 2 x RJ45 Gbe LAN RJ45
- IP66 foran
- Vesa-feste 100x100
- 319x245x51,7 mm
- 1 x 3 pins DC 9 ~ 36Vdc
- Windows IoT-støtte



SPECIFICATIONS

Back-up	:	UPS battery 21W/10.8W/1.95Ah OPTION!
Approval	:	CE / FCC, Class A / UL
Dimensioner	:	319x245x51.7mm
Driftstemperatur	:	0~50°C / -20~60°C (option)
Ethernet	:	2 X RJ45 GbE
Forsyning	:	DC 9~36Vdc MAX 47W
Kontrast	:	1500:1(800x600), 1000:1(1024x768) (1000 nits 700:1)
Lyd	:	line out
Montering	:	Panel Mount, Vesa mount 100x100
Opløsning	:	MAX 800x600 /1024x768
OS SUPPORT	:	Windows IOT
Porte	:	1 x DB-9 RS-232/422/485, COM1 (Default RS-232) 1 x RS-232 DB-9, COM2

IPP12-IX-1000N

SPECIFICATIONS

Touch	:	Needs to be ordered! Resistive, Projected capacitive or glass
USB	:	2 x USB 3.0 type A
Vekt	:	2.6Kg