

Vifteløst system, 9./8. generasjons i7/i5/i3 Celeron®-processor, Intel® Q370, USB, RS232, VGA, HDMI, DIN-MOUNT

FEATURES

Industriell vifteløs Celeron, i3/i5,i7 CPU-støtte (LGA 1151)
Gen. 8/9
Chipset Q370
1x RS232/422/485. VALGFRI! ISOLERT RS232/422/485, Må bestilles separat!
4 USB 3.1 Gen. 2
2 x USB2.0
1 x USB (intern, 180D type A for lisensnøkkel, opptil 30 mm)
2 x ETH Intel i211-AT & i219-LM (Alternativ! flere kan bestilles)
VGA, HDMI-utgang
19~30Vdc
: veggfeste eller DIN-feste
83,4x192x230 mm (BxHxD)
Arbeidstemperatur -10°C til +60°C, OBS KREVER RAM OG SSD også spesifisert for -10°C til +60°C
Bestill separat!
OS-støtter Windows 10 og Linux



SPECIFICATIONS

CPU	:	9th/8th gen Intel® Core™ processor, up to 65W
Chipset	:	Q370
USB	:	4 x USB 3.1 Gen 2 2 x USB 2.0 1 x USB 2.0 (internal, 180D type A for license key, up to 30mm
Driftstemperatur	:	-10°C to +60°C (+14°F to +140°F) with Intel®, 9th/8th gen Intel® Core™ and W.T. HDD/SSD
BIOS	:	AMI
Approval	:	CE/FCC
Ethernet	:	2 x 10/100/1000 Mbps (Intel® i211-AT & i219-LM) OPTION! More LAN ports available from extension I/O modules
Hukommelse	:	2 x DDR4-2666/2400 MT/s un-buffered SO-DIMM, up to 64GB
Materiale	:	Aluminum extrusion heavy-duty cold-rolled steel
Montering	:	Wall mount as option, DIN mount as option
Mål og vægt	:	Weight (net/gross) 3.82 kg (8.43 lb)/4.78 kg (10.55 lb)
OS SUPPORT	:	Windows® 10, Linux



SPECIFICATIONS

Spænding	:	Type: ATX/AT Input: 24 VDC (uMin=19V/uMax=30V)
Udgange	:	1 x VGA 1 x HDMI
AMT	:	12
Dimensioner	:	Dimensions (W x H x D) 83.5 x 192 x 230 mm (3.28" x 7.54" x 9.04")

