

Innebygd CPU-kortformat 3,5" i5 gen. 8/9, VGA, DP, HDMI, LVDS trippelskjermstøtte, 2xRJ45, 6x USB, 4x COM

FEATURES

- Integrert Intel® 8. og 9. generasjons Intel® Core™ H-serie prosessor
- 2 x DDR4 SO-DIMM 2666 MHz opptil 64 GB
- Integrert VGA, DisplayPort, HDMI, LVDS for støtte for trippelskjerm
- 1 x Intel® Gigabit PHY LAN
- 1 x Intel® Gigabit LAN
- 1 x MiniPCle (støtter mSATA)
- 1 x M.2 (nøkkel E)
- 2 x SATA3
- 4 x USB 2.0
- 4 x USB3.1 Gen2
- 4 x COM
- 1 x GPIO
- 1 x PS/2
- Støtte Watchdog Timer
- Støtte 4K-oppløsning
- DC-inngang 9~35V
- 20°C ~ 60°C



SPECIFICATIONS

CPU	:	I5 8th & 9th Gen Core™ H-series Processors. Package Type: FCBGA1440
Chipset	:	Intel® QM370
USB	:	4xUSB 2.0, 4xUSB3.1 Gen.2
Driftstemperatur	:	Operating within 0 ~ 60°C Storage within -20 ~ 80°
Ethernet	:	1 x Intel® i219-LM Gigabit PHY LAN(Support iAMT 12.0), 1 x Intel® i210-AT Gigabit LAN
Forsyning	:	DC input 9~35V
GPIO	:	Onboard programmable 8-bit digital I/O interface
Grafik	:	Intel® UHD Graphics, VGA, HDMI, Sisplay POrt
Luftfugtighed	:	10%~90%, non-condensing
Lyd	:	Realtek ALC262 HD Audio
SATA	:	Intel® QM370 built-in 2 x Serial ATA3 interface up to 600MB/s Support RAID 0, 1 and Intel Rapid Storage Technology.
Watchdog	:	Generates a system reset with internal timer for 1min/s ~ 255min/s



**DANBIT**

BK3.5-I5-GEN89

SPECIFICATIONS

Dimensioner : 3.5" 146x101mm(lxW)



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.